



|                          |                                |
|--------------------------|--------------------------------|
| Luminous Flux (Lumen)    | 4950                           |
| Luminous Efficacy (lm/W) | 110                            |
| Power factor             | >0.90                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | PC (Polycarbonate)             |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                             |
|------------------------|-----------------------------|
| Mounting Method        | Surface                     |
| Cut out (mm)           | 250                         |
| IP-rating              | IP65                        |
| Impact Protection (IK) | IK06 - 1 joule              |
| Operating Temperature  | -20 to +40                  |
| Housing                | Aluminium                   |
| Colour of the Fixture  | White                       |
| Colour of material     | White                       |
| Fixture Connection     | Terminal, 3-Pole (L, N, PE) |
| Series                 | DOWNLIGHT SURFACE IP65      |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 125 |
| Diameter (mm) | 250 |

## Why Any-lamp?

## Sensor Information

 Type of sensor

Order from the **largest lighting specialist** in Europe

No Sensor

 **Customised** quotation



Up to **7 years warranty**



**Easy** return process